

	NEW E-5008	NEW E-5008	NEW E-5008	NEW E-5008
MOTOR	ELECTRIC 210	ELECTRIC 320 Dual Motor AWD	ELECTRIC 230 Long Range	HYBRID 136 e-DCS6
Electric motor technology Front / Rear	Synchronous with permanent magnet	Synchronous with permanent magnet	Synchronous with permanent magnet / -	NA
Displacement (cm <sup>3</sup> )	NA			
Number of cylinders / arrangement	NA			
Number of valves per cylinder	NA			
Maximum power in kW (or hp)	157 (210) from 3935 to 14000 rpm	240 (320) cumulated: 157 (210) front from 4370 to 14000 rpm 83 (110) rear from 4760 to 14000 rpm	170 (230) from 4740 to 14000 rpm	100 (136) at 5500 rpm
Maximum torque (Nm)	345 from 250 à 4370 rpm	Front: 343 from 250 to 4370 rpm Rear: 166 from 0 to 4760 rpm	343 from 250 to 4740 rpm	230 at 1750 rpm
<b>TRANSMISSION</b>				
Type	single-speed gearbox	single-speed gearbox	single-speed gearbox	6 speed automatic gearbox
Ratio Front / Rear	9,77 / -	9,77 / 12,396	9,77 / -	NA
<b>BATTERY</b>				
Technology	Lithium-ion NMC	Lithium-ion NMC	Lithium-ion NMC	Lithium-ion NMC
Useful Capacity (kWh)	73	73	98	0,43
Weight (kg)	520	520	574	12,1
Tension (V)	400	400	400	48
<b>MASSES &amp; CHARGES</b>				
Kerb weight (kg)	2218	-	-	1705
Gross vehicle weight (kg)	2900	-	-	2350
Maximum braked trailer weight 12% slope (kg)	1000	-	-	1000
<b>PERFORMANCES</b>				
Maximum speed (kph)	170	-	-	200
• 1,000 m standing start	30,7	-	-	33,6
• 400 m standing start	17,1	-	-	18,2
• 0 to 100 kph	9,7	-	-	11,3
In-gear acceleration (seconds)				
• 30 to 60 kph	2,5	-	-	3,1
• 60 to 90 kph	3,1	-	-	4,3
• 80 to 120 kph	6,1	-	-	7,2
<b>RANGE &amp; CONSUMPTION</b>				
Range in WLTP combined (km)	502	500*	660*	NA
Range in WLTP city (km)	-	-	-	NA
Consumption in WLTP cycle combined (kWh / 100 km)	-	-	-	NA
Consumption in WLTP cycle city (kWh / 100 km)	-	-	-	NA
Consumption in WLTP cycle combined (L / 100 km)	NA	NA	NA	5,8
CO2 emissions in WLTP cycle combined (g / km)	NA	NA	NA	131
Niveau sonore en mouvement (dB)	-	-	-	-
<b>CHARGE (20°C from 20% to 80%)</b>				
On board charger AC (kW) - Standard/Option	11/22	11/22	11/22	NA
DC maximum Capacity (Kw maxi) - Standard	160	160	160	NA
Charging time Wallbox 11 kW AC (h)	4,50	-	-	NA
On board charger 11 kW	7	-	-	NA
Charging time Wallbox 7,4 kW AC (h)	7	-	-	NA
On board charger 11 Kw	30	-	-	NA
Charging time Super Charger DC (mn)	30	-	-	NA
<b>WHEELS</b>				
Type of tyres (standard or option, depending on version)	235/55R19 235/50R20	235/55R19 235/50R20	235/55R19 235/50R20	225/55R19
Spare wheel	Standard: Tire repair kit	Standard: Tire repair kit	Standard: Tire repair kit	Standard: Tire repair kit
Turning diameter between sidewalks (m)	11,2			
<b>BRAKES &amp; SUSPENSION</b>				
Type of front/rear brakes	Ventilated Front discs: 365x37mm Front Brake Caliper double pistons Ventilated Rear discs: 356x26mm	-	-	Ventilated Front discs: 330x30mm Front Brake Caliper 60mm piston Ventilated Rear discs: 330x14mm
Type of front suspension	pseudo Mac-Pherson			
Type of rear suspension	multi-link			twist beam
<b>DIMENSIONS (mm)</b>				
Overall length	4791			
Width	1895			
Kerb height	1694			
Wheelbase	2901			
Front overhang / Rear overhang	940 / 950			
Front track / Rear track	1630 / 1636			
Ground clearance	204	204	189	194
<b>BOOT</b>				
Boot volume (dm <sup>3</sup> ) - VDA V210 behind row 2	748	-	-	748
Boot volume (dm <sup>3</sup> ) - VDA V210 behind row 3	259	-	-	259
Boot volume (dm <sup>3</sup> ) - VDA V214 behind row 1	1815	-	-	1815
<b>AERODYNAMICS</b>				
SCx drag area (m <sup>2</sup> )	0,77	-	-	0,805

\* WLTP cycle under approval